

Narrow Aisle BS Spring Loaded Steps



Max Load
150 Kg



British
Made

Robust, hardworking narrow aisle units with spring loaded castors. All welded construction. Spring loaded castors allows the feet to lower to the ground under operator's weight. Treads are formed sheet steel with choice of ribbed rubber or anti-slip surface. All colour finishes are hard wearing powder coated.



British Standard
Safety Steps



KM 608967
BS EN 131-7

Treads (inc platform)	2	3	4	5
Platform height mm	500	750	1000	1250
Overall height mm	1455	1705	1950	2200
Platform width mm	406	406	406	406
Platform depth mm	406	406	406	406
Overall width mm	500	500*	500*	500*
Overall depth mm	640	820	1090	1240
Weight kg	15	20	24	28
Ribbed Rubber treads				
Order Ref	S400	S402	S404	S406
Anti-slip treads				
Order Ref	S401	S403	S405	S407
Stabilisers	No	Yes	Yes	Yes
Width with stabilisers	N/A	1085	1085	1085

Colour Options	GN	R	B	Y	GY	S	O	W
----------------	----	---	---	---	----	---	---	---



Tread Clamps

Ribbed rubber treads models are supplied complete with tread clamps ensuring high visibility and preventing edges from peeling.

*With stabilisers retracted.



Steptek