Steptek Quality Extra Heavy Duty Stability Base Model

Hand built with attention to detail, both in design and manufacture, to ensure total reliability and many years of arduous operation. Over load tested to 200kg.

Construction: Welded heavy gauge steel box section and bar. Fitted with hand lock lever anchorage; when locked, the front feet rest firmly on the floor, feet fitted with protective grey non-marking rubber feet. Safety warning bar fitted to protrude in front of steps, linked to hand lock lever mechanism, to deter users from climbing steps when still in 'mobile' mode.

Stability base model: Outboard wheels mounted on splayed base frame gives superior stability.

Finish: Main structure red epoxy finish; safety bar and hand lever mechanism in safety yellow.

Wheels: Front 2 swivel castors with 100mm diameter rubber tyred wheels, with roller bearings. 2 rear axle mounted 200mm diameter wheels with rubber tyres and roller bearings.

British Standard Safety Steps

A caution notice is fitted to remind user of operation procedure. A health and Safety at Work information sheet is supplied.



S945





Max Load

British Made

See page 25 for optional extras.



Tread options:



Ribbed Rubber



Expamet



KM 608967 BS EN 131-7

Tread width: 490mm | Platform W x D: 540 x 500mm

Number of Treads Including Platform	Average Working Height	Platform Height	Overall Dimension (H x W x D) mm	R/Rubber Treads Order Ref	Kg	Expamet Treads Order Ref	Kg
3	2190mm	690mm	1690 x 780 x 955	S920	56	S940	48
4	2420mm	920mm	1920 x 850 x 1120	S921	64	S941	56
5	2650mm	1150mm	2150 x 910 x 1290	S922	74	S942	62
6	2880mm	1380mm	2380 x 960 x 1425	S923	93	S943	81
7	3110mm	1610mm	2610 x 1010 x 1610	S924	102	S944	89
8	3340mm	1840mm	2840 x 1060 x 1790	S925	112	S945	99
9	3570mm	2070mm	3070 x 1140 x 1955	S926	122	S946	109
10	3800mm	2300mm	3300 x 1220 x 2130	S927	136	S947	124
11	4030mm	2530mm	3530 x 1270 x 2290	S928	145	S948	132
12	4260mm	2760mm	3760 x 1270 x 2290	S929	157	S949	143
13	4490mm	2990mm	3990 x 1370 x 2455	S930	168	S950	153
14	4720mm	3220mm	4220 x 1540 x 2790	S931	180	S951	165
15	4950mm	3450mm	4450 x 1565 x 2975	S932	192	S952	177

 $^{^{*}10}$ tread and above supplied in 2 halves for transport purposes. Refer to page 25 for optional extras

