KG			
Max Load	British		
150 Kg	Made		

S682

Front feet fitted with protective plastic floor pads. Expamet treads and large working top platform makes them ideal for loading and unloading items outside.

Wheels: 2 front swivel castors with 100mm diameter rubber tyred wheels with roller bearings, 2 rear axle-mounted 200mm wheels with rubber tyres and roller bearings.

Finish: All steelwork red epoxy or galvanised finish.

## Tread width 750mm / Platform W x D: 750 x 1200mm

No. of Treads	Average working	Platform height	Overall (H x W x D)	Red Expamet		Galvanised Expamet	
(inc platform)	height mm	mm	mm	Order Ref	Wt. Kg	Order Ref	Wt. Kg
3	2190	690	1680 x 960 x 1680	S680	80	S690	80
4	2420	920	1910 x 960 x 1870	S681	89	S691	89
5	2650	1150	2140 × 960 × 2060	S682	98	S692	98
6	2880	1380	2370 x 960 x 2250	S683	107	S693	107
7*	3110	1610	2600 × 960 × 2440	S684	116	N/A	N/A
8*	3340	1840	2830 x 960 x 2630	S685	125	N/A	N/A



Welded steel tube and bar construction. Expamet treads and large working top platform makes them ideal for loading and unloading items outside. The steps have 2 handles at the front fitted with knuckle guard hand grips for safe lifting and moving.

Wheels: 2 rear 200mm steel centred wheels with rubber tyres and roller bearings.



British Standard Safety Steps



## Tread width 500mm / Platform W x D: 500 x 600mm

No. of Treads Average		Platform Overall		Blue Expamet		Galvanised Expamet		1	0-1	Option
(inc platform)	working height mm	height mm	(H x W x D) mm	Order Ref	Wt. Kg	Order Ref	Wt. Kg		14	Inward opening gate on
3	2250	750	1760 x 650 x 1345	S701	36	S711	36	i /	(C2)	platform end. Ref: S700 (Extr
4	2500	1000	2010 x 850 x 1535	S702	41	S712	41			
5	2750	1250	2260 x 1050 x 1725	S703	46	S713	46		Annen Harris	
6	3000	1500	2510 x 1250 x 1915	S704	51	S714	51			



\*7 & 8 tread versions have bolt on handles for transport purposes.



