

COMMERCIAL - KNA RANGE - NARROW AISLE PRO MOBILE STEPS

Our Narrow-Aisle Pro Range is perfect for use where space is at a premium! We have upgraded our narrow range to have a 450mm wide treads, which has maximised stability for the user. These steps are still light weight and are easy to manoeuvre.



KNA05DM

KNA Narrow Aisle Pro Mobile Steps

This range comes fully welded and ready to go! Manufactured from mild steel and with toe plate to all sides of the platform. Complete with a super high gloss powder coated finish and a brightly coloured braking system (for an additional safety feature). The smaller models come with 4 plunger castor feet which means the unit can turn in its own space, with larger models having our signature central braking system.

Suitable for use in archives, warehouses (with aisle racking) and office environments.

| | |
|----------------------|--|
| Platform Height (mm) | 500mm - 2000mm High |
| Tread Width (mm) | 450mm Wide x 200mm Deep |
| Platform Size (mm) | 450mm Wide x 400mm Deep |
| SWL (Kg) | 300 |
| Braking System | 2 - 4 Tread : Plunger Castors 5 - 8 Tread : Central Lever Brake |

Dimensions & Information

Working Height - This is shown as a general guide between waist height and just above the shoulders of the average person, approximately 750mm range.

Overall Width - The main framework of the step is 500mm wide; the overall width shown is taken at the widest point, the axle, at the rear of the step.

Platform Size - As standard this consists of two treads giving a total working area of 450mm x 400mm deep. This can be extended (View Options & Extras).

Kick Plate - All steps have kick plate to all three sides of platform.

Packing Information - When your step arrives with you, it will be fully assembled. It will have a small amount of foam protection on the top pulpit rail.

| CODE | No. Of Treads | PLATFORM Height (mm) | WORKING HEIGHT (mm) | OVERALL DIMS. H x W x L (mm) | WEIGHT (Kg) |
|--------|---------------|----------------------|---------------------|------------------------------|-------------|
| KNA 02 | 2 | 500 | 1500 - 2250 | 1500 x 590 x 735 | 24 |
| KNA 03 | 3 | 750 | 1750 - 2500 | 1750 x 590 x 735 | 33 |
| KNA 04 | 4 | 1000 | 2000 - 2750 | 2000 x 590 x 920 | 45 |
| KNA 05 | 5 | 1250 | 2250 - 3000 | 2250 x 630 x 1150 | 57 |
| KNA 06 | 6 | 1500 | 2500 - 3250 | 2500 x 630 x 1360 | 64 |
| KNA 07 | 7 | 1750 | 2750 - 3500 | 2750 x 630 x 1510 | 72 |
| KNA 08 | 8 | 2000 | 3000 - 3750 | 3000 x 630 x 1580 | 80 |

NOTE: All dimensions and weights are approximate only. Klime-Ezee reserves the right to change / amend any dimensions without prior notice.

Change of brake type from standard may affect the overall width of the unit, should you require any further information, please contact us.