

## **TekA Step Single Ended Access Platform** **500kg Capacity**

TekA Step single ended access platforms are high quality access platforms ideal for warehouse access or maintenance work and give a comfortable working space for the operator and their tools or materials.

They feature handrails on both sides of the steps with a side opening on either side (Right Hand Side opening is default - if you require LHS please specify. Double Safety Chains can be added across the opening). The platform can be operated easily using the hand lever which immobilises and mobilises the steps. Available in a range of sizes.

A fully welded construction with a simple hand lever braking systems makes this platform both robust and practical to use in most environments and to suit most industrial applications

Painted Finish is supplied as standard, for a galvanised finish contact our sales team for a quotation

**\*\*We can offer a platform height modification if you require a size that is not available as standard on the dropdown list. Please use the dropdown to select the size slightly over your required size (eg. required size 2100mm choose 2286mm) and add the Platform Height Modification from Optional Extras dropdown then quote the size you require in the notes section on the payment page.**

Standard Platform Size W x D: 762x1600mm

All TekA Steps Are UK Manufactured.



## **TekA Step Single Ended Access Platform Specifications**

Code	Platform Height mm	Overall Dimensions (HxWxD) mm	No of Treads
TS2133/30/3	762	1712 x 965x 1981	3
TS2133/30/4	1016	1966 x965x 2134	4
TS2133/30/5	1270	2220 x 965 x 2286	5
TS2133/30/6	1524	2474 x 965 x 2438	6
TS2133/30/7	1778	2728 x 965x 2591	7
TS2133/30/8	2032	2982 x 991 x 2743	8
TS2133/30/9	2286	3236 x 1016 x 2896	9
TS2133/30/10	2540	3490 x 1092 x 3048	10
TS2133/30/11	2794	3744 x 1167x 3200	11
TS2133/30/12	3048	3998x 1243 x 3352	12
TS2133/30/13	3302	4252 x 1319 x 2500	13

All Welded steel construction

Punched metal treads

Handrails either side of steps and 950mm over platform

Kick plate as standard on 7 treads and over

Hand lever locking bar to mobilise unit

Rubber tyred wheels and nylon castors

Rubber covered feet

Step width 762mm

Step rise: 250mm

Standard Platform Size (without options) W x D: 762x1600mm

Certified Load capacity: 500kg

**Please Note:** All Dimensions are approximate and shown in mm